

DS50 D | Glass and dishwasher

SKU: 2559

ADDITIONAL INFORMATION

Weight	65 kg
Dimensions	660 × 660 × 1010 mm
Brand	DIHR
Packaging dimension (Wi)	660
Packaging dimension (De)	660
Packaging dimension (He)	1010
External size (Wi)	595
External size (De)	610
External size (Hi)	845
Gross weight (kg)	6.5
Voltage (V/Hz)	400/50
Power (W)	5200
Water consumption per cycle (l)	2.3
Basket dimensions (mm)	500 x 500
Washing up efficiency (basket/hour)	30
Tank capacity (l)	27
Duration of the cycle (mp)	120/180
Maximal dish size (mm)	325
Net weight (kg)	61



PRODUCT DESCRIPTION

The DS 50 double-walled glass and dishwasher with AISI 304 stainless steel exterior and interior, heat- and sound-insulated double-walled door, LED panel, opening sensor safety microswitch, deep-drawn basin (27.0 liters), uniform system of overflow and drain pipes washing pump for triple protection), non-return valve, built-in rinse aid dispenser, "Thermostop" system (rinsing only starts when the water in the boiler reaches 85 ° C), boiler capacity: 5.7 liters, electronically controlled, sewage dispenser without pump (with gravity discharge). Glasses up to 310 mm high and max. Suitable for 325 mm plates. Basket size: 500x500mm. Accessories: 2 baskets (for glasses and plates), 1 cutlery basket. The base unit is available in 400V / 50Hz, but is optionally available in 230V / 50Hz.

The use of a water softener is mandatory!

ADDITIONAL INFORMATION

Weight	65 kg
Dimensions	660 × 660 × 1010 mm
Brand	DIHR
Packaging dimension (Wi)	660
Packaging dimension (De)	660
Packaging dimension (He)	1010
External size (Wi)	595
External size (De)	610
External size (Hi)	845
Gross weight (kg)	6.5
Voltage (V/Hz)	400/50
Power (W)	5200
Water consumption per cycle (l)	2.3
Basket dimensions (mm)	500 x 500
Washing up efficiency (basket/hour)	30
Tank capacity (l)	27
Duration of the cycle (mp)	120/180
Maximal dish size (mm)	325
Net weight (kg)	61

