

GRANULES 900 TR PLUS Frontal loading | Granules warewasher

**SKU:** 22450

### **ADDITIONAL INFORMATION**

<b>Weight</b>	353 kg
<b>Dimensions</b>	1020 × 1210 × 2240 mm
<b>Brand</b>	<a href="#">DIHR</a>
<b>Packaging dimension (Wi)</b>	<a href="#">1210</a>
<b>Packaging dimension (De)</b>	<a href="#">1020</a>
<b>Packaging dimension (He)</b>	<a href="#">2240</a>
<b>External size (Wi)</b>	<a href="#">1095</a>
<b>External size (De)</b>	<a href="#">910</a>
<b>External size (Hi)</b>	<a href="#">2100</a>
<b>Gross weight (kg)</b>	<a href="#">353</a>
<b>Voltage (V/Hz)</b>	<a href="#">400/50</a>
<b>Power (W)</b>	<a href="#">13000</a>
<b>Water consumption per cycle (l)</b>	<a href="#">4,4</a>
<b>Basket dimensions (mm)</b>	<a href="#">735 x 240</a>
<b>Washing up efficiency (basket/hour)</b>	<a href="#">15</a>
<b>Tank capacity (l)</b>	<a href="#">103</a>
<b>Duration of the cycle (mp)</b>	<a href="#">5/7/9/11/13/16</a>
<b>Net weight (kg)</b>	<a href="#">320</a>



## PRODUCT DESCRIPTION

Features of the Granules Warewasher:- The washing system is covered by an International Dual Patent- Twelve wash cycles, six of which combine water detergent and granules- Soft-touch panel with multicolour key - Functional LCD Display for a constant control of all operations - Multi language control panel- Double-wall body, fully insulated with high performance thermo-acoustic material- AISI 316 body and impeller, high performance wash-pump - Wash-tank in AISI 316 S/S with guaranteed homogeneous thickness - Double, vertical easy-fit wash-arms, with concave nozzles to prevent clogs and to optimize the combined flow of water and granules- All electric and electronic components are sheltered in a dedicated box, for easy access from the machine's front - It is placed on a rotating support stand, to optimise the mechanical action of the granules on the surfaces to wash- Granules collection strainer, with right-level mark for granules- The resistant lower part of the door becomes a perfect working surface, simplifying the load/unload operations- The optional service trolley facilitates the loading/unloading of the machine, increasing the operation speed and, consequently, the machine's productivity- Heat recovery unit, to optimize energy resources and cut down on steam and wamodulThe TR system is a heat exchanger: the moist warm water vapour is drawn directly out of the machine when the door is closed, and used for preheating the cold water. As a result, the energy required to reach the final rinse temperature (approx. 85 °C) is dramatically reduced. The heat exchanger reduces the exhaust air temperature by more than half. Humidity volume is decreased if

compared with the equivalent machine without heat recovery unit. This permanently improves the operators' comfort. tank's capacity: 120 l boiler's capacity: 20 l water consumption per cycle: 5,5 l basket's size: 850x350

## ADDITIONAL INFORMATION

<b>Weight</b>	353 kg
<b>Dimensions</b>	1020 × 1210 × 2240 mm
<b>Brand</b>	<a href="#">DIHR</a>
<b>Packaging dimension (Wi)</b>	<a href="#">1210</a>
<b>Packaging dimension (De)</b>	<a href="#">1020</a>
<b>Packaging dimension (He)</b>	<a href="#">2240</a>
<b>External size (Wi)</b>	<a href="#">1095</a>
<b>External size (De)</b>	<a href="#">910</a>
<b>External size (Hi)</b>	<a href="#">2100</a>
<b>Gross weight (kg)</b>	<a href="#">353</a>
<b>Voltage (V/Hz)</b>	<a href="#">400/50</a>
<b>Power (W)</b>	<a href="#">13000</a>
<b>Water consumption per cycle (l)</b>	<a href="#">4,4</a>
<b>Basket dimensions (mm)</b>	<a href="#">735 x 240</a>
<b>Washing up efficiency (basket/hour)</b>	<a href="#">15</a>
<b>Tank capacity (l)</b>	<a href="#">103</a>
<b>Duration of the cycle (mp)</b>	<a href="#">5/7/9/11/13/16</a>
<b>Net weight (kg)</b>	<a href="#">320</a>



