

RX104E | Rack conveyor dishwasher

**SKU:** 15655

### **ADDITIONAL INFORMATION**

<b>Weight</b>	345 kg
<b>Dimensions</b>	1005 × 2100 × 2030 mm
<b>Brand</b>	<a href="#">DIHR</a>
<b>Packaging dimension (Wi)</b>	<a href="#">2100</a>
<b>Packaging dimension (De)</b>	<a href="#">1005</a>
<b>Packaging dimension (He)</b>	<a href="#">2030</a>
<b>External size (Wi)</b>	<a href="#">1900</a>
<b>External size (De)</b>	<a href="#">805</a>
<b>External size (Hi)</b>	<a href="#">1830</a>
<b>Gross weight (kg)</b>	<a href="#">345</a>
<b>Voltage (V/Hz)</b>	<a href="#">400/50</a>
<b>Power (W)</b>	<a href="#">19900</a>
<b>Basket dimensions (mm)</b>	<a href="#">500 x 500</a>
<b>Number of baskets</b>	<a href="#">83-107</a>
<b>Washing up efficiency (basket/hour)</b>	<a href="#">83-107</a>
<b>Maximal dish size (mm)</b>	<a href="#">450</a>
<b>Net weight (kg)</b>	<a href="#">245</a>



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The RX 104 E continuous dishwasher has an electronic control panel, a washing and rinsing zone. AISI 304 material grade stainless steel exterior and interior, heat and sound insulated double wall door, opening sensor with safety microswitch. With digital display, fault diagnosis and electronic control

(IPX5 protection). Washing direction: from right to left. The dishwasher has stainless steel wash and rinse arms that are easy to remove and clean. The tanks in the washroom have stainless steel filters that can be easily removed without removing the wash arms to keep the water clean and free of food residue. The device can be operated in two gears: 83 or 107 baskets / hour. When not in use, the machine automatically stops the conveyor and switches to standby mode. When incoming baskets are detected, the system restarts, thus avoiding wasting water and energy. The system provides constant water pressure for an optimal rinsing cycle. The non-return valve prevents water from flowing back and infiltrating in the event of an external pressure drop. Basket size 500x500mm (usable width / height: 510mm / 450mm), water consumption: 130 liters / hour. Optional features: • 4.5kW drying module that dries linearly or at an angle - at 90 ° - with high-pressure preheated air. This guarantees perfectly dry dishes. • Heat recovery module for cold water supply. The appliance recovers and reuses the heat (hot steam) / energy generated by the machine to preheat the cold water. The use of a water softener is mandatory!

## ADDITIONAL INFORMATION

<b>Weight</b>	345 kg
<b>Dimensions</b>	1005 × 2100 × 2030 mm
<b>Brand</b>	<a href="#">DIHR</a>
<b>Packaging dimension (Wi)</b>	<a href="#">2100</a>
<b>Packaging dimension (De)</b>	<a href="#">1005</a>
<b>Packaging dimension (He)</b>	<a href="#">2030</a>
<b>External size (Wi)</b>	<a href="#">1900</a>
<b>External size (De)</b>	<a href="#">805</a>
<b>External size (Hi)</b>	<a href="#">1830</a>
<b>Gross weight (kg)</b>	<a href="#">345</a>
<b>Voltage (V/Hz)</b>	<a href="#">400/50</a>
<b>Power (W)</b>	<a href="#">19900</a>
<b>Basket dimensions (mm)</b>	<a href="#">500 x 500</a>
<b>Number of baskets</b>	<a href="#">83-107</a>
<b>Washing up efficiency (basket/hour)</b>	<a href="#">83-107</a>
<b>Maximal dish size (mm)</b>	<a href="#">450</a>
<b>Net weight (kg)</b>	<a href="#">245</a>



